

## TM40 Touch Interface Module



### Features

- Thin, sleek design
- Intuitive, icon-based interface via touchscreen, with quick menu-driven prompts
- 4.3-inch (10.9 cm) brilliant and vivid widescreen color display
- Compatible with EVO (V2.16 or higher), MG5000/MG5050, SP5500/SP6000/SP7000 (version 4.72 or higher), and SP4000/SP65 (version 4.90 or higher)
- Optional: supports up to 32 floor plans (EVO), or 8 floor plans (MG/SP)
- Optional: supports Annunciator mode
- Customizable labels: zones, areas, users, and PGM outputs
- Controls up to 8 PGM outputs
- Supports WinLoad, not NEware
- External micro SD card slot for firmware upgrades and uploading photos etc.
- Built-in indoor temperature sensor
- 1 zone/temperature input to connect a detection device or exterior temperature sensor (TEMP07)
- Available in multiple languages
- Clean screen mode: locks screen for easy cleaning
- Display: 5.4 x 9.5 cm (2.1 x 2.7 in.) with a resolution of 480 x 272 pixels
- Surface-mount installation only; dimensions: 12.4 x 8.1 x 1.6 cm (4.9 x 3.2 x 0.7 in.)
- Available in 3 finishes: brushed aluminum, brushed black anodized, and brushed white anodized